

Sierra Premium™





Sierra Premium™ Shake - Caramel



Sierra Premium™ Shake - Mahogany



Sierra Premium™ Smooth



Sierra Premium™ Shake - Charcoal Gray



Sierra Premium™ Shake - Maple



Sierra Premium™ Shake - Painted



Sierra Premium™ Shake - Mahogany



Sierra Premium™ Shake - Macadamia



Sierra Premium™ Smooth - Painted



Sierra Premium™ Smooth - Painted



Sierra Premium™ Shake - Mahogany

Sierra Premium™

- Sierra Premium™ panels are 60% thicker than other fiber cement shake panels. Thicker panels mean more distinctive appearance and deeper shadow lines.
- Deep grain and groove texture creates an authentic shake appearance for residential and commercial applications.
- Less breakage during installation with thicker 1/2" panels.
- Boards are factory primed and sealed on six sides.
- Withstands greater than 150 mph (3 second gusts) sustainable winds¹ - ASTM E 330.
- Available in primed, pre-finished in 8 stain colors or with a one or two coat finish in any color.
- Backed by a lifetime limited warranty*. Finish warranties: 25-year 2-coat finish, 15 year 1-coat finish or 12-year stain finish warranty by Duckback Products, Inc.*

Sierra Premium™ Shake

Sierra Premium™ Smooth



Caramel



Charcoal Gray



Emerald Wheat



7" profile
(shown lapped)




Macadamia



Mahogany



Maple



8-3/4" profile
(shown lapped)



Redwood**



Weathered Gray**



Primed

Silica Dust Warning: NICHHA products contain crystalline silica [a.k.a. sand, silicon dioxide], which is a common Earth's naturally occurring mineral. Inhalation of crystalline silica into the lungs and repeated exposure to silica, can cause health disorders, such as silicosis, lung cancer, or potentially death depending upon various factors. To be conservative, Nichiha recommends that whenever drilling, cutting, sawing, sanding or abrading the product, users must observe the following safety practices. 1] Use best work practices to reduce airborne dust concentrations. 2] Use a fiber cement circular saw with a dust collector for cutting (e.g., Makita 5057KB). The dust collector must be connected to a HEPA vacuum. 3] Do not use compressed air for cleaning dust. 4] Work outdoors where feasible, otherwise use mechanical ventilation. 5] Everyone handling Nichiha products or in the vicinity of others using Nichiha products must wear safety glasses and properly fitted respirators prior to handling Nichiha products. Nichiha requires that users wear a **NIOSH/OSHA approved respirator with a rating of N100, O100, P100, or R100** in accordance with applicable government regulations and manufacturer instructions. 6] All employers must comply with the OSHA PEL and ACGIH TLV-TWA. 7] Warn others in area. These requirements are designed to help minimize exposure to crystalline silica. We also require that you read all instructions and warnings [including MSDS] prior to using NICHHA's products. For further information or questions, please consult the MSDS or your employer. The MSDS for Nichiha products are available at www.nichiha.com, at your local Nichiha dealer or through Nichiha directly at 1.866.424.4421. FAILURE TO ADHERE TO OUR WARNINGS, MSDS, AND OTHER INSTRUCTION MAY LEAD TO SERIOUS PERSONAL INJURY OR DEATH.

FIBER CEMENT AT ITS BEST and SIERRA PREMIUM are trademarks of Nichiha USA, Inc.
 *See Nichiha Warranties for detailed information on terms, conditions and limitations.
 **Special order colors that require longer lead times.
 †See NichiProducts™ Installation Guidelines for Application and Fastener requirements.
 NOTE: Printed material may not accurately depict actual product color.
 ©2009 Nichiha USA, Inc. All rights reserved. Printed in the USA. DG 01.09 25K NM-4000



Nichiha USA, Inc.
 6659 Peachtree Industrial Blvd.
 Suite AA,
 Norcross, GA 30092
 Toll Free: 1.86 NICHHA 1
 866.424.4421
 P. 770.805.9466
 F. 770.805.9467
nichiha.com

Fiber Cement At Its Best™