

## Regular Drywall

### General Purpose Drywall

#### Description

Lafarge Regular Drywall is designed for interior wall and ceiling applications. The board is available in several thicknesses and edge treatments to meet most general construction needs. It contains a non-combustible gypsum core and is covered with paper facings on the front (ivory), back, and long edges. This product will accommodate a variety of decorative treatments after proper surface preparation.

Lafarge Regular Drywall can be used in building applications that require direct mechanical attachment to wood or metal wall and ceiling frames, or attachment to existing surfaces using fasteners or adhesives. May also be used as a thermal barrier in roof assemblies when specified by the roofing manufacturer.

While Lafarge Regular Drywall has some inherent fire resistance characteristics, this product should not be used to provide the levels of fire resistance required by various building codes and standards. For fire resistance, use Lafarge Firecheck® products. When properly sealed and used in a certified sound rated assembly, Regular Drywall will contribute to required sound transmission classification (STC) values.

Note: Lafarge Regular Drywall is suitable for interior applications only, and should not be used where temperatures exceed 125°F for extended periods or in areas of extreme humidity. Likewise, the board should be protected from exposure to adverse conditions during storage and construction.

#### Physical Characteristics

**Core:** Non-combustible, dimensionally stable, inert gypsum

**Paper:** 100% recycled; front and edges = ivory, back = gray

**Long Edges:** Tapered in all sizes, rounded or square in 1/2 in.

#### Available Sizes:

Nominal thickness	1/4 in.	3/8 in.	1/2 in.
Nominal width	4 ft	4 ft	4 ft 54 in.
Standard length	8 ft	8 ft to 12 ft	8 ft to 16 ft
Nominal weight	1.1 lbs/ft <sup>2</sup>	1.3 lbs/ft <sup>2</sup>	1.6 lbs/ft <sup>2</sup>

#### Standards and Codes

Lafarge Regular Drywall is formulated to perform in accordance with ASTM C 36 and C 1396; \*\*Federal Specification SS-L-30d, Type III, Grade R; and CAN/CSA-A82.27-M.

#### Technical Specifications

**UL** classified for surface burning

(File No. R16102)

(tested in accordance with ASTM E 84)

Flame spread = 10; Smoke developed = 0

**Core combustibility**

(tested in conformance with ASTM E 136)

Non-combustible

#### Installation

Install according to Gypsum Association GA-201, GA-216, or ASTM C 840. Refer to GA-214 for finishing recommendations.

#### Handling Recommendations

Stack flat, keep dry, and lift (do not drag) to avoid scuffing. Avoid damage to edges. For detailed recommendations, refer to GA-216 and GA-801.

#### Safety Precautions

Wear safety glasses and NIOSH-approved respirators during cutting, breaking, rasping, or other dust-producing activities.

Material Safety Data Sheets (MSDS) are available for all Lafarge products upon request.

\*The federal specification for gypsum board, SS-L-30d was withdrawn in 1984. It is provided here for information only and should not be referenced for new construction.

Job Name: \_\_\_\_\_

Contractor: \_\_\_\_\_

Date: \_\_\_\_\_

09/06



**Lafarge North America Inc.**  
Herndon, Virginia 20170  
Orders and inquiries  
(800) 237-5505

**Lafarge Canada Inc.**  
Montreal, Quebec H3B 1L7  
Orders and inquiries  
(866) 649-7786

www.lafargenorthamerica.com